

# ***SPLASHDRONE 3+***

## *User Manual v1.40*

Check [www.swellpro.com](http://www.swellpro.com) for the latest version of this manual and firmware updates for your drone and camera.



Thank you for purchasing the SwellPro SplashDrone3+. We have designed and manufactured the SplashDrone to the highest quality standards. With proper care and maintenance you should enjoy your SplashDrone for many years.

Like any marine equipment, long-life and trouble-free operation relies on due care and maintenance. With proper care and maintenance you should enjoy your drone for many years. After flying in salt or contaminated water, always thoroughly rinse and dry your SplashDrone in fresh water immediately after use or before salt and sediment can dry inside moving parts.

It is important to familiarize yourself with the features of this unique drone by carefully studying this manual and particularly the priority sections indicated in the Table of Contents. Check [www.swellpro.com](http://www.swellpro.com) for the latest manuals, software and tips. Refer to the Version Information section at the end of this manual which details additions and corrections to this manual.

### Icons Used in This Manual



Read first



Prohibited



Important Notice



Operating Tip

### Other Information

Visit and subscribe to SwellPro's YouTube channel for instructional videos and product information.



Join our facebook group exclusive to SplashDrone users




[www.facebook.com/swellpro/](https://www.facebook.com/swellpro/)


### Register your Product Warranty

Please ensure you register your product as soon as possible to ensure warranty coverage.  
[www.swellpro.com/](http://www.swellpro.com/)



# Contents

Reading Notes	02
Icons Used in This Manual	02
Other Information	02
Register your Product Warranty	02
Product Overview 	05
The SplashDrone 3+	06
Drone Components	07
Remote Controller Components	08
Remote Controller Screen controls	09
FPV Screen Interface	10
Drone Indication Lights	11
Drone Landing Gear	12
Propellers	13
Batteries	14
Flight Modes 	15
Flight Modes	16
Return Home	17
Preparing for Flight 	18
Preparing for Flight	19
Preparation before your First Flight (or in a new location)	19
Accelerometer (Gyroscope) calibration	19
Compass Calibration	21
Preparation Before Every Flight	24
Remote Controller	25
Remote Controller Overview	26
Low Battery Alarm Warnings	28

Flight 	29
Introducing You to Flying a Drone	30
Flying the SplashDrone 3+	30
Default Flight Restrictions	30
Starting / Stopping the Motors	31
Basic Flight Steps	32
Water Take-offs and Landings	33
Power-Flip	33
Take-offs and Landings from a Boat	34
Advanced Settings	35
Video Transmitter Channel Selection	36
Remote Controller Pairing (to the drone)	37
Conversion of the Remote Controller Throttle Position	38
Remote Controller Joystick Calibration	39
Appendix	40
Specifications	41
Warranty Information	42
FLIGHT BATTERY -Safety Guideline	42
Safety Operation Guideline & Disclaimer and Warning	45
Safe Operation Guidelines	45
Disclaimer and Warning	48
Version Information	50

## Product Overview

---



This section identifies the different parts of the drone, controller and accessories and describes how to assemble the drone.

Enhancing and extending the features of the previous SplashDrone 3, the latest SplashDrone 3+ is the most reliable and versatile waterproof drone yet.


Coupled with several different payload accessories such as cameras, low-light sensors or release mechanisms, your SplashDrone 3+ can be adapted for a wide variety of uses. It is an all-purpose, all-weather, waterproof flying platform.

The SplashDrone 3+ allows you to operate in most weather conditions, in tough environments, whether over land or over the sea. With its advanced modular design it can quickly adapt to all type of missions from aerial filming to search and rescue, ocean survey, fishing and many more applications.


### WARNING:


The SplashDrone 3+ utilizes high voltage LiHV battery technology in the drone battery. The battery charger supplied with the SplashDrone 3+ is only suitable for charging SwellPro LiHV batteries and the LiPo batteries for the SplashDrone 3+ remote controller.

Charging non-LiHV, low voltage LiPo batteries (including the batteries for the older SplashDrone 3) with the LiHV charger is dangerous and may cause the battery to catch fire or explode.



- |   |  |
|---|--|
| [01] Cover/hatch screw  | [08] Accessory quick-release screw                   |
| [02] Quick release carbon fiber propellers  | [09] Waterproof cable plug/socket                    |
| [03] Nose direction markers   | [10] Rubber foot                                     |
| [04] Flight Indication Lights - Front: 2 X Green LED<br>Stern: Tri-colour Drone Status Lights | [11] Waterproof brushless motor                      |
| [05] Antenna pod  | [12] Propeller Attachment system                     |
| [06] Payload accessory space (camera illustrated)   | [13] GPS top cover/hatch                             |
| [07] Landing gear   | [14] Drone Status Light visible<br>through top cover |





- |  |  |   |
|--|--|---|
| <p>[01] Remote Antenna<br/>For drone control signal<br/>2.4GHz</p> <p>[02] Left pairing button<br/>For binding the RC with<br/>the drone</p> <p>[03] Accessory Control<br/>Wheel<br/>Function depends on the<br/>accessory used</p> <p>[04] Camera switch<br/>Used for controlling Video<br/>and Photo functions.</p> <p>[05] Airdrop switch<br/>Opens and closes the payload<br/>release</p> <p>[06] Left Joystick<br/>Controls the drone's ascent<br/>(up), descent (down) and/or<br/>to rotate the aircraft nose<br/>left or right (Yaw).</p> <p>[07] Working Status Indicator<br/>Remote controller status</p> <p>[08] Left power button<br/>Press the left and right<br/>power buttons<br/>simultaneously to<br/>power on the controller</p> <p>[09] USB Port /Interface<br/>For remote controller firmware<br/>upgrade</p> | <p>[10] Hanger ring<br/>Attachment point for neck<br/>lanyard</p> <p>[11] Right power button<br/>Press the left and right power<br/>buttons simultaneously to<br/>power on the controller.</p> <p>[12] Power status Indicator<br/>Displays the remote<br/>controller's battery status</p> <p>[13] Right Joystick<br/>Controls the drone direction<br/>of flight</p> <p>[14] Return-Home switch<br/>Commands the drone to<br/>return automatically</p> <p>[15] Flight mode switch<br/>GPS / Cruise Flight / ATTI</p> <p>[16] Gimbal Vertical Tilt<br/>wheel<br/>Adjusts the vertical tilt of<br/>the camera</p> <p>[17] Right pairing button<br/>For binding the RC with<br/>the drone</p> <p>[18] Video antenna<br/>Receives FPV live video<br/>5.8GHz</p> | <p>[19] FPV screen<br/>Displays FPV live video and<br/>On Screen Data (OSD) from<br/>the drone.</p> <p>[20] Smooth+ Yaw switch<br/>Activates the Smooth+<br/>Yaw control</p> <p>[21] Smooth+ Yaw control<br/>Fine control of drone<br/>rotation (yaw) when<br/>Smooth+ yaw is active</p> <p>[22] Smooth+ Pan switch<br/>Activates the Smooth+<br/>Pan control</p> <p>[23] Smooth+ Pan control<br/>Fine control of lateral<br/>drone movement (pan)<br/>when Smooth+ Pan is<br/>active</p> |
|--|--|---|




## Remote Controller Screen Controls

### Power Button

The screen will automatically power on with the remote controller, but can be manually powered off.

### Auto search/Menu Select

Use the auto search function to select the most suitable channel / Switch between the different menus




The FPV screen of the Remote Controller provides realtime flight information as well as images from the drone if a camera accessory is fitted. The SplashDrone 3+ uses 5.8GHz video transmission technology to reduce transmission delays to a minimum. The 5.8G range can reach over 1.6km and has 40 channels available to select from. See the Advanced Settings section of this manual for configuration details.

**⚠ Before turning on the Remote Controller, ensure all switches are in their uppermost (top) position or the Remote Controller will not complete its power up-sequence and will sound a constant alarm.**

## Remote Controller LED Indicators

Working Indicator	Power Status Indicator	Warning Tone	
Solid Green	Solid Green		Status is good
	RED Light ON	No	Remote Controller battery low
	RED slow flash	Yes	Remote Controller battery is dangerously low
Slow Flash		Yes - once	Remote controller and drone receiver disconnected
Fast Flash		Success tone	Pairing

**⚠ When the remote controller battery level becomes very low, the remote controller power status light will slowly flash red and sound a warning tone. If this occurs, please land the drone as soon as possible. If the Remote Controller loses power during flight, the drone will automatically return to its home point and land.**



- |   |   |
|---|---|
| <p>[01] <b>Battery Voltage</b><br/>Drone battery voltage</p> <p>[02] <b>Return Home direction</b> &lt;---&gt;<br/>Dynamically displays the relative angle between the nose and the return point. When the mark is displayed in middle of the FPV screen, it means the nose of the drone is facing the return point.</p> <p>[03] <b>Artificial Horizon</b><br/>Displays the angle of roll of the drone</p> <p>[04] <b>Distance</b><br/>The horizontal distance between the drone and the home point.</p> <p>[05] <b>Height</b><br/>The vertical height of the drone above the home point elevation</p> <p>[06] <b>Flight Safety Warning</b><br/>FS is displayed when the drone is automatically landing for low battery or other safety issues</p> <p>[07] <b>Flight Mode</b><br/>GPS: GPS Mode<br/>ATT: ATTI Mode<br/>CIR: Smart Cruise</p> | <p>[08] <b>Time</b><br/>Flight time since last motor start</p> <p>[09] <b>Ascent speed</b> ↑ <b>Descent speed</b> ↓<br/>The vertical speed of the drone when ascending or descending, units are metres/second</p> <p>[10] <b>GPS reception</b><br/>Number of GPS/GLONASS satellites being used for positioning</p> <p>[11] <b>Velocity</b><br/>The drone's current horizontal speed</p> <p>[12] <b>Yaw Compass angle</b><br/>The compass heading of the drone</p> <p>[13] <b>Pitch</b><br/>The drone's current angle of nose pitch</p> <p>[14] <b>Roll</b><br/>The drone's current angle of roll</p> <p>[15] <b>LOW Battery warning</b><br/>Visual warning to return the drone as battery voltage is low. This symbol will start flashing if battery voltage becomes critical and the drone will start auto landing in place.</p> |
|---|---|

## Drone Indication Lights











The fuselage of the drone includes a pair of green nose LED indicator lights and a pair of status indicator lights on the rear arms.









The nose LED indicator lights are always lit and are used to indicate the direction of the nose of the drone. The rear aircraft status lights indicate the current status of the flight control system by flashing patterns of red, green and yellow lights.

Please refer to the following table for the different messages.

### Drone Status Indicators

Flight Modes		
	One Green Flash	ATTI Mode
	Two Green Flashes	GPS Mode
	Three Green Flashes	Circling flight & Smart Cruise (Optional)
	Four Green Flashes	Cruise Flight
	Green Fast Flashing	APP control/ Return Home
GPS Status		
	No Red light	Good GPS signal
	One Red Flash	Satisfactory GPS signal
	Two Red Flashes	Poor GPS signal
	Three Red Flashes	No GPS connection, or no GPS signal
Low battery warnings		
	Three Yellow Flashes	First level low battery warning, for safety, land as soon as possible.
	Yellow Fast Flashing	Second level low battery warning, the drone will start it's auto landing sequence.

## Warnings and Abnormal Status


	Red - Fast Flashing	Lost radio signal
	Yellow, Green alternate slow flashing	Compass interference detected
	Alternating Red & Green slow flashing	Lost GPS signal, GPS abnormal
	Alternating Red and Yellow - slow flashing	IMU (accelerometer) vibration has exceeded its limits, or is abnormal
Other		
	Red, Green, Yellow alternate flashing	Initialization process after powering on
	Red solid ON	Motors cannot be armed

Some additional flashing patterns are used for special conditions such as calibration.

## Drone Landing Gear




The SplashDrone 3+ has two carbon fibre landing frames that raise the drone and propellers above most ground obstacles and also protect any accessories mounted under the drone body.

Each landing gear frame is installed by inserting one leg at a time. Push one leg firmly all the way into the socket. Then insert the second leg of the frame into its socket, applying slight pressure against the first leg to align the second leg with its socket. Make sure the legs are fully inserted into the sockets. The legs are held in place by the the flexing pressure of the legs.



Insert the landing gear one leg at a time, according to the red arrows. Ensure the legs are fully inserted.

The SplashDrone 3+ has two pairs of propellers - two clockwise propellers and two counter-clockwise propellers. The hub of each motor shows the type of propeller used for that motor. Propellers cannot be attached to the wrong motor by accident.



- ⚠ Always place one hand under the motor to support it when installing or removing propellers. Failure to provide this support could result in bending or breaking the landing gear.

### Attaching and Removing Propellers:

1. Check that the propeller rotation (CW or CCW) matches the motor hub. This is the normal direction the propellers spin during flight.
2. Rotate the propeller in the hub until it engages, then push the propeller downwards and rotate it 1/8th of a turn opposite to its name to lock it.
3. Check the propeller is completely locked by checking that the dots on the propeller and hub align or by holding to motor hub firmly and ensuring that the propeller cannot be turned.
4. To remove propellers, support the motor with one hand and press the propeller down and then rotate it 1/8th of a turn according to its name to unlock it from the hub.

⚠ The blades are sharp, please be careful to avoid personal injury.

⚠ Prior to each flight, please check that the propellers are smooth all over and are correctly installed and securely fastened.

The SplashDrone 3+ has two batteries required for operation. One battery powers the drone, the other powers the drone remote controller.

It is important to charge the batteries before use and install them correctly.

### Drone Battery Installation

When inserting the battery, observe the following precautions:

- Hold the battery velcro and drone power cable out of the way as the battery is inserted.
- Insert the battery with care with its cables on the left-hand side of the drone.
- Observe the label on the battery
- Please observe the instructions and the arrow on the label.



⚠ Once connected to the drone, the battery cables and connectors must be placed in the space between the battery and the rear case of the drone.

### Remote Controller Battery Installation

The Remote Controller battery is located behind a hatch on the back-side of the unit.

To open the hatch, apply slight downward pressure to the hatch and slide it open. When installing the battery, be careful to align the battery connectors properly. Incorrectly connecting the battery will damage the remote controller and void the warranty. Close the battery hatch by aligning the hatch and sliding it closed.

### Low temperature precautions

1. In low temperature environments (-10C degrees to 5C degrees) , flight time will be reduced. Ensure batteries are fully charged and kept warm (20~30C) before use.
2. Also be aware that the low battery warnings will provide less warning time, so land the drone as soon as the first battery warning appears.

⚠ The SplashDrone 3+ Battery Charger MUST NOT be used to charge older LiPO technology ⚠ batteries such as SplashDrone 3 batteries. Using an incorrect charger can cause a battery to catch fire or explode.

## Flight Modes

---



This section introduces the drone and its functions.

## Flight Modes


The SplashDrone 3+ utilizes an improved flight control system, incorporating 3 of the best flight modes.


**GPS mode:** This mode uses the GPS module to achieve accurate and stabilized hovering, braking, intelligent flight, intelligent return and other intelligent flight mode functions. In this mode, maximum flight speed is 10m/s, maximum ascend speed is 4m/s, and maximum descend speed is 3m/s.


**Smart Cruise:** Specially designed for smooth aerial filming. The turning function of the left joystick is disabled, and is blended into the right joystick function, to achieve smooth sweeping turns with a single control.

**ATTI mode:** This is a more advanced flight mode which does not use the GPS positioning function but still maintains altitude stabilization. The drone will drift with any wind when hovering and will not brake when the joysticks are released.

---

 In both ATTI and GPS mode, it is recommended to wait for at least 9 GPS satellites before take-off to ensure that the home point is correctly registered for the Return Home function to operate.

 In ATTI mode the drone's speed is faster and auto braking is disabled. Ensure the drone has sufficient space for the pilot to turn or brake. For emergency braking, with sufficient GPS coverage in ATTI mode, switch to GPS mode and release the joysticks.

 Select the preferred flight mode of the drone using the remote mode switch on the controller.



---

## Return Home

The SplashDrone 3+ has an Auto Return Home function if the GPS successfully recorded the home point before takeoff. If the remote controller and the aircraft lose communication with each other, the drone will automatically return to the take off point and land. The Return Home function can also be manually initiated from the remote controller by using the Return Home switch.



## Return Home Process

Flare maneuver	Description
	If the drone's height > 20 Metres* and distance from Home Point > 15 Metres, the drone will maintain its altitude and return to its Home Point.
	If the drone's height < 20 Metres* and distance from Home Point > 15metres, the drone will climb to 20 Metres* and then return to its Home Point.

\* The Return Home altitude default is 20 Meters, but can be changed to another altitude by using the SwellPro Assistant software.

- ⚠ If the GPS signal is poor (fewer than 5 satellites) or GPS doesn't work, the Return Home function will not be available.
- ⚠ The Accuracy of the return home is determined by the nature of the GPS/GLONASS system and the quality of the GPS signal at the drone's location. The pilot must not assume that the drone will return to the exact departure point as some variation in GPS signals is normal for all GPS-based systems.
- ⚠ Note: During the return process, the joysticks are disabled. To fine-tune the landing site or return to manual control of the drone, place the Return Home switch in the Normal position.

## Preparing for Flight

---



This section describes how to prepare your drone for flight.

Before every flight, it is important to prepare your drone properly.

This section is presented in two sections:

1. Preparation before your **first flight**  
(or when the drone is more than 100km from its last flight location)
2. Preparation before **every flight**.

The drone relies on very sensitive sensors to control flight positioning and stability. The accelerometer (gyroscope) and compass sensors need to be calibrated before flying in a new location or if the drone has suffered undue shock or excessive vibration.

Accelerometer calibration is necessary if:

- a. The drone is brand new.
- b. The drone has been flown extensively in in ATTI mode.
- c. When in GPS flight mode and using only the THROTTLE joystick, the drone drifts at an angle.
- d. The drone has been subjected to heavy shaking during transportation.
- e. If after successfully performing a compass calibration, the drone Status Indicators are solid red when trying to arm (unlock) the motors.

## Accelerometer Calibration Process

1. Place the drone on a horizontal surface. Power on the remote controller then the drone.
2. After hearing a drone power up tone, switch to "Return-Home" mode on the controller.
3. Hold the left joystick into the lower right corner\*(45°) and the right joystick into the upper right corner\*(45°) position.



Return Home




Switch and Joystick commands for Accelerometer Calibration\*

- \* If you have reconfigured your Remote controller for Mode 3 - right hand throttle, the position is left joystick to the upper right corner and the right hand joystick to the lower right corner (45°)
4. The Drone Status Lights will start fast blinking red-green-yellow indicating that calibration is underway. When the Status lights go solid green, release the joysticks to complete the calibration.



Red, Green, Yellow  
fast flashing

Calibrating Accelerometer



Green ON

Calibration Successful

## Compass Calibration

Compass calibration is necessary if:

- The drone is brand new.
- The drone is more than 100km from the location of its last flight.
- The YAW (Y) indication on the Remote Controller screen does not show the correct compass reading (North = 0°, South = 180°)  $\pm 10^\circ$
- The drone has been subjected to strong magnetic fields
- The drone has been crashed or dropped accidentally
- The drone sways or drifts excessively during hover in GPS mode
- The drone Status Indicators are solid RED when trying to arm (unlock) the motors.

Note: Flying close to any magnetic interference is HIGHLY DISCOURAGED. Fly a good distance away from high-voltage power transmission lines, powerful radio and television towers, large metal structures, etc.

### Compass Calibration Processes

There are two ways to calibrate the compass: a fast and simple method or a more accurate complete calibration process. Of course, if time permits, the more accurate calibration process is recommended.

#### Simple Two-Sided Compass Calibration Process


Compass Calibration is performed with the drone outdoors and away from any sources of magnetic interference such as metal structures, radio masts or mobile phones.



- Place the drone on a horizontal surface. Remove propellers and accessories. Power on the controller then the drone. Close the top GPS hatch cover.
- Watch the Drone Status Indicator through the top GPS hatch cover of the drone.
- After hearing a drone power up tone, rapidly switch the Flight Mode switch backwards and forwards between the three modes until the Drone Status Indicator turns YELLOW.



**Two-Sided Compass Calibration Switch Command**  
Rapidly switch backwards and forward between flight modes

#### Simple Two-Sided Compass Calibration

	Yellow ON	Horizontal Calibration
	Green ON	Vertical Calibration
	Red ON	Calibration Failed
	Alternating - Red, Green, Yellow slow flashing	Calibration Successful

Calibration Step	Description
	<p>1. Holding the drone <b>horizontally</b>, rotate the drone around you in a <b>clockwise direction</b> until the the Drone Status Indicator changes from YELLOW to GREEN. You can see the Drone Status Indicator through the top hatch cover.</p>
	<p>2. Hold the drone <b>nose-down</b>, facing away from you so you can see the Drone Status lights on the underside of the body. Rotate the drone <b>clockwise</b> until the Status Lights start blinking red-green-yellow. Then the calibration is complete.</p> <p>If the calibration procedure was not successful, the Drone Status Lights will glow RED for 3 seconds.</p> <p>Power OFF the drone, wait a few moments and then power ON the drone.</p>

If the calibration is unsuccessful, you will need to repeat the calibration. If a two-sided simple calibration is not successful, it may be necessary to do a complete, six-sided calibration.

### Complete Six-Sided Calibration Process


Compass Calibration is performed with the drone outdoors and away from any sources of magnetic interference such as metal structures, radio masts or mobile phones.

1. Place the drone on a horizontal surface. Power on the controller then the drone.
2. After hearing a drone power up tone, switch to "Return-Home" mode on the controller.
3. Hold the **left joystick into the lower left corner\***(45°) and the **right joystick into the upper left corner\***(45°) position. The Drone Status Indicators will fast-flash Red-Green-Yellow.



### Switch and Joystick commands for Complete Compass Calibration\*

- \* If you have reconfigured your Remote controller for Mode 3 - right hand throttle, the position is left joystick to the upper left corner and the right hand joystick to the lower left corner (45 °)




Compass Calibration must be completed within 90 seconds and while the Drone Status Indicators are fast-flashing Red-Green-Yellow.


4. Holding the drone **horizontally**, rotate the drone around you in a **clockwise direction** one full rotation (360 degrees).




5. Turn the drone **upside-down**, then rotate the drone around you in a **clockwise direction** one full rotation (360 degrees).




6. Turn the drone **nose up**, then rotate the drone around you in a **clockwise direction** one full rotation (360 degrees).



7. Turn the drone **nose right (3 o'clock)**, then rotate the drone around you in a **clockwise direction** one full rotation (360 degrees).



8. Hold the drone **nose-down**, then rotate the drone around you in a **clockwise direction** one full rotation (360 degrees).



9. Turn the drone **nose left (9 o'clock)**, then rotate the drone around you in a **clockwise direction** one full rotation (360 degrees).



**10.** Place the drone down and wait for the Drone Status Indicators to stop flashing Red-Green-Yellow.

**11.** Switch the Return Home switch back to the Normal position.

**12.** Power OFF the drone, wait a few moments and then power ON the drone.

Calibration is successful if the motors will Arm (power on) in GPS mode with Good GPS coverage. If the Drone Status Indicators glow RED when you attempt to arm the drone, then calibration has not been successful.



Alternating - Red, Green,  
Yellow slow flashing

Six-sided Calibration mode

## Preparation Before Every Flight

Drones are fun to fly, but they are not toys. Be a responsible pilot and prepare for your flight properly to fly safely and get the most out of your SplashDrone 3+. Follow this checklist before every flight.

- Are all batteries charged?
- Is calibration required?
- Are propellers secured properly?
- Is the payload accessory securely fastened and properly connected?
- Are the Drone Status Indicator lights showing errors?
- Is The GPS hatch properly closed?
- Are all switches on the remote in the UP position for takeoff?
- Are there at least 10 satellites for GPS flight and Return Home functions?
- Is the drone battery showing at least 16v?
- Are antennas pointing down and out for best reception?
- After take-off always check hover stability at low altitude.
- After flights on salt or dirty water, always thoroughly rinse all moving parts in fresh water.




## Remote Controller

---

This section introduces the remote controller functions.

---

 The default remote controller configuration is for left hand throttle. If you prefer to have right hand throttle, please consult the Advanced Settings section of this manual.

---

## Remote Controller Overview


The SplashDrone 3+ Remote Controller operates using two frequency bands, 2.4GHz and 5.8GHz. 2.4GHz is used for drone control and 5.8GHz is for the FPV video signal. The controller also incorporates control functions for payload accessories such as cameras and release devices.

### Power ON and Power OFF




1. Ensure ALL switches are in the UP (top) position.
2. Press and hold both power switches for 3 seconds. The Remote Controller will power ON.
3. To turn OFF the Remote Controller, return the Camera Control switch to the Preview position to stop any recording.  
Press and hold both power switches for 3 seconds. The Remote Controller will power OFF.

### Airdrop Switch




OFF: Close Airdrop release  
Airdrop: Releases the payload

### Camera Control





Video: Record Video  
Preview: Preview  
Photo: Take Picture


### Flight Mode



GPS: GPS mode  
Smart Cruise: Smart Cruise Mode  
ATTI: ATTI mode

Return Home	
	<p>Normal: Return Home is disabled</p> <p>Return-Home: Activate Return Home</p>


Gimbal Control	
	<p>Tilt Control Wheel: Controls the gimbal tilt</p> <p>Pan Control Wheel: Controls the pan or roll of the gimbal</p>

Smooth+ Control	
	<p>Engage our new Smooth+ controls to switch from joystick to fine knob control of drone movement. Your flight and footage will be instantly smoother as you dial in just the right amount of turn or bank. Easily setup a smooth transition or dial in an orbit. Even if you are new to drone controls, you can fly as smoothly as a pro.</p>


## Drone Control

### Mode 1\* - Left hand throttle- (American/European configuration)

#### Left Joystick



#### Right Joystick



\* If you have reconfigured your Remote controller for Mode 3 - right hand throttle, the functions of the joysticks is reversed.

## Low Battery Alarm Warnings

The SplashDrone 3+ has three battery alarm levels:


**Level 1 alarm:** The drone battery level has reached 14.6V.

The FPV screen will display a large battery icon in the middle of the screen to prompt you to return the drone if it is not nearby and prepare to land. The Drone Status Indicators on the rear arms will flash a pattern of 3 yellow lights.

**Level 2 alarm:** The drone battery level has reached 14.4V. The battery icon on the FPV screen will flash. The battery level is now below 20%.

**Level 3 alarm:** The drone battery level has reached 14.2V. After 10 seconds, the drone will initiate in-place Auto Landing to protect the drone and battery. The LED on the rear arms will flash yellow constantly. The FPV will display "FS" in the lower-left corner to indicate that flight-safety mode is active.

Should it be necessary to prevent the Auto-Landing, switch the drone into ATTI mode to regain manual control and land the drone.



- 
- ⚠ During flight it is important to constantly monitor the battery voltage as flying conditions like strong wind and fast movements can deplete the battery more rapidly.
  - ⚠ It is dangerous to continue flying the drone with insufficient battery power. This could result in damage to the battery and risk of the drone crashing.
-

## Flight



This section introduces and discusses flying hazards, flight restrictions and planning.

## Introducing you to Flying a Drone

If this is your first time flying a drone, please read this manual thoroughly and watch the instructional videos on our YouTube channel. We recommend taking professional training and guidance. When flying, select an environment appropriate to your skills.


It is advisable for all drone pilots to become familiar with flying in ATTI mode in case of GPS or magnetic interference which can interfere with drone controls.

## Flying the SplashDrone

1. Although the SplashDrone 3+ is waterproof, do not fly in fog or if the wind is very strong or gusting above Beaufort Force 6.
2. Select an open place or water surface as an ideal flying site.  
Flying between or near large steel buildings could adversely affect the workings of the compass and can adversely affect or block GPS and control signals.
3. During flight, try to maintain line of sight with the drone, keep away from obstacles and people.
4. Do not fly near high voltage power lines or communication towers which may interfere with the remote controller of the drone.
5. Flying higher than 4000 meters above sea level, environmental factors including air density reduce the performance of aircraft and therefore also propulsion batteries.

## Default Flight Restrictions

According to provisions of the International Civil Aviation Organization and many national air traffic regulations, drones must be operated in specified airspace. By default the SplashDrone 3+ is configured to not exceed an altitude of 250m the Home Point altitude. This and other parameters can be reconfigured if necessary by utilising the SwellPro Assistant software.



 When flying in ATTI mode, there are no Geofence Limitations.

### Precautions Before Unlocking the Motors:

- Place the drone in an open area at least 3 meters away from you and others.
- For safety, always stand upwind and to the side of a drone for takeoff and landing.
- While the drone is completing its power-on self-check, please keep the drone stationary.
- In GPS flight mode, the motors cannot be armed (started) until there are at least 9 satellites for position control. In ATTI flight mode, there is no need to wait to unlock the motors.
- Rotate four motors by hand before flying to check whether the motor is jammed or not. When the aircraft is unlocked and the motor rotates, we can see whether the speed of the four motors is uniform. If one or more motors rotate not well, cannot fly the drone by force. Remove the propeller and check whether there is any object in the motor.

### Unlocking the Motors

Pull both the left and right joysticks simultaneously down and inwards and maintain this position for 3 seconds. The motors will now be unlocked, and will start rotating.

Normal



### Switch and Joystick command to Arm Motors

If the motors **will not arm in GPS mode with more than 9 satellites, but will arm in ATTI mode**

The drone may sense compass or gyroscope interference. This may be due to situations such as a rocking boat or nearby magnetic interference. In this case, it is possible to carefully take-off in ATTI mode and then switch to GPS mode.

If the SplashDrone **will not arm in ATTI mode**, refer to the calibration section elsewhere in this manual.

If the SplashDrone **arms in ATTI mode but then shuts down**, power down and restart the drone to reset the Flight Controller.

## Locking/Stopping the Motors

To lock the motors: Pull both the left and the right joysticks downwards and outwards. Alternatively, if the drone has landed, it is also possible to hold the throttle in the minimum position for 3 seconds.



### Switch and Joystick command to Lock Motors

---

**⚠ The motors can be stopped in an emergency.** Stopping the motors whilst airborne may cause the drone to crash and should only be carried out in emergencies (for example: there is a risk that the drone may hit people or crowds) if stopping the motors will minimize any potential damage.

---

## Basic Flight Steps

1. Check that the drone is correctly assembled, propellers are tight and the main hatch is sealed.
2. Power on the remote control, followed by the drone.
3. Place the drone on a flat open surface or on the surface of the water.
4. Wait for the FPV screen to display the camera's live video and the OSD flight data. Check that the flight display is normal.
5. Check the following flight data:
  - Battery voltage > 16volts
  - Satellites > 9
  - Yaw (Y) indicates the drone's current compass direction.
6. For safety, you should stand upwind and to the side of the drone and at least 3 metres distant.
7. Arm the motors in GPS mode.
8. Push the THROTTLE joystick up slowly, allowing the drone to take off smoothly. Release the throttle when the drone is approximately 1.5m high. Allow the drone to hover for a moment to ensure flight stability.
9. Always use gradual, smooth joystick movements.
10. When you need to descend, slowly pull down the throttle joystick, allowing the drone to descend and land on a flat surface or on the water.
11. After safely landing, keep the throttle down in its lowest position for at least 5 seconds until the motors have stopped or use the disarm joystick command.
12. Stop recording video before powering down the drone, followed by its remote controller.




## Water Take-offs and Landings

1. When taking off from choppy water, ascend quickly from the surface to prevent the drone being affected by a passing wave.
2. When landing on water, descend vertically to the surface. If the drone lands with horizontal speed, it is possible the drone can flip and be inverted. The flight controller will shut down the motors if the drone becomes inverted.

⚠ Do not leave the drone floating inverted for more than a few minutes.  
Flip the drone using the Power-Flip command or recover the drone as soon as possible to avoid water entering the drone.

## Power-Flip

If the drone becomes inverted on the surface of the water, using the Power-Flip feature, the drone can be flipped so that it is right-side up.



### Joystick command to Power-Flip the SplashDrone 3+


With the drone floating upside-down, pull the left-hand (throttle) joystick straight down to the minimum and simultaneously push the right-hand joystick either up, down, left or right depending on the direction of flip required.

## Take-offs and Landings from a Boat

When taking off from a boat there needs to be sufficient space, otherwise the drone should be placed on the water for take-off. Likewise, it is safer and easier to land the SplashDrone on the water beside the boat rather than landing on a rocking boat or where there is insufficient space for a safe landing.

If the boat is rocking, the SplashDrone 3+ may not arm its motors in GPS mode. In this case, carefully take-off in ATTI mode and then switch to GPS mode if there are sufficient satellites.

---

 For safety, it is not recommended to launch or land your SplashDrone from your hands.

---

Be aware of the direction of the wind relative to the boat. Even when at anchor, it is possible that the wind will not be at the nose of the boat.


Always try and take off with the wind so that the drone will be taken away from the boat. When landing the drone onto a boat, if possible land against the wind so that the drone will be held away from the boat. The Smooth+ controls of the SplashDrone 3+ are useful to finely control and balance the drone position.

## Advanced Settings

---

This section describes advanced settings for the drone and its settings

Selecting the channel (there are a total of 40 channels)



### Channel Selection

After powering on the transmitter, it will initially display the currently selected frequency band, followed by the current channel, and, in the lower right corner, a red dot flashing indicating the currently selected transmission power level as described above.

For example: To set up channel E5:

1. Long press the button for 3 seconds, it initially enters band selection mode and will automatically scroll between the bands (A, B, C, D, E), When it reaches "E", short press the button to choose E band.
2. To adjust channel to E5, short press the button 4 times. When the display shows frequency band E and channel 5, long press the button for 2 seconds, the dot in the lower right corner will flash once to confirm the selection, release the button. On completion, the system will display "E" first, followed by "5", and finally the dot will flash representing the transmission power level.

### Remote Controller Pairing (to the drone)

1. Connect the jumper (which is supplied with the drone) into the B/VCC channel of the remote receiver located inside the drone. Then power on the drone, the receiver red light will flash fast and indicates the start of the pairing sequence.
2. Hold either left or right pairing button (No.2 or 17), then power on the remote controller. When the left indicator turns solid red, pairing mode is active. Release the buttons when the indicator changes to solid green. Pairing is successful.
3. Power OFF the drone and remove the Jumper cable from the receiver.



When the pairing is completed, remove the JUMPER on the receiver's B/VCC channel.

---


### Conversion of the Remote Controller Throttle Position

The Remote control's default joystick configuration is the American/European - Left handed throttle. However, it is possible to set Japanese configuration - which is right hand joystick for throttle/yaw control.

Remote Controller Joystick conversion method :

1. Using both index fingers, hold both joysticks in the upper right position at 45 degrees.
2. Now, using both thumbs, simultaneously press the power buttons to start the controller.
3. The left led will flash indicating the current joystick configuration setting.
4. Press the left pairing button and the left led will flash once for mode 1, flash 2 times for mode 2, 3 times for mode 3 and 4 times for mode 4.

After the successful re-configuration of the right throttle setting, the right joystick is the throttle and roll, the left joystick is the Yaw and pitch.



Joystick configuration	The left led will flash
Mode1 : Left hand throttle	1 Green Flash
Mode2: Not used	2 Green Flashes
Mode3: Right hand throttle	3 Green Flashes
Mode4: Not used	4 Green Flashes


---

⚠ After the successful re-configuration of the right throttle setting, the right joystick is the throttle and roll, the left joystick is the Yaw and pitch.

---

### Remote Controller Joystick Calibration Method

1. Make sure that all toggle switches are at the top, the left and right joystick are kept at 45 degrees below the left, and press the left and right power button to start. Enter the remote joystick calibration status (left status indicator flash).
2. Move the left and right joystick to the highest and lowest positions respectively (one round or two round), then return to the center, then turn the left and right wave wheels to the left and the right respectively, and then return to the center.
3. After the operation is completed, press the right pairing button and wait for about 30 seconds. The remote controller will send out the normal boot tone. The calibration is successful. The left indicator will flash slowly and enter the normal working mode. If the calibration is fail, the left indicator will continue to flash. Every time the right pairing button is pressed, an alarm signal will be sent out. It needs to be calibrated again.
4. Power off the remote, and then power on.



- 
- ⚠ The Remote calibration is complete when the throttle calibration is done.
  - ⚠ Before commencing calibration, please make sure that all the toggle switches are set to the top position.
-

## Appendix

---



## Specifications

### Aircraft

Waterproof Level:	Surface Buoyant (short periods up to 600mm deep)
Drone Weight:	1447g (without battery)
Axis Diameter:	450mm
Max Ascend Speed:	4m/s
Max Descend Speed:	3m/s
Max Flight Speed:	20m/s (ATTI mode)
Max Flight Altitude:	200m (GPS) / 1.3km (ATTI)
Max Flying Wind Speeds:	a. Typical Maximum = 8m/s (11-16knots)(F4) b. Typical Gusts = 12m/s (22-27Knots) (F6) Peak
Hovering Precision:	±0.5meter
Max Flight Time (per charge):	20 ~ 23 minutes
Max Flight Range:	1.6km
Max Flight Weight:	3KG
Max Payload Capacity:	1KG
Positioning Satellite:	Dual Satellites - GPS/GLONSS
Flight Controller:	Swellpro S3
Motor:	#3510/620KV
ESC:	40A
Propellers:	#1242 carbon fiber quick-fit propellers
Working Temperature:	-10°C ~ 40°C
Battery Types:	4S 15.2V 5200mAh LiHV battery
Battery Weights:	561g (5200mAh LiHV)
Charging Time:	90 minutes

### Remote Control

Weight:	660g
Frequency:	2405 ~ 2475HMZ
Range:	1.6km (unobstructed, free of interference)
Receiver Sensitivity(1%PER):	-105dbm
Working Current:	160-300mAh
No. of Channels:	10
Battery:	2S 7.4V 2300mAh lipo battery

FPV Screen	
Frequency:	5645 ~ 5965HMZ
Screen Size:	5inch
Resolution:	800X480Pixels
Brightness:	500 cd/m <sup>2</sup>

## Warranty Information

Please visit [swellpro.com](http://swellpro.com) for the latest information on:

Swellpro's Warranty policy

Swellpro's Maintenance service policy

Click on the Buyer Registration to complete the registration to activate the after sales warranty (this is very important, it will ensure that your equipment is covered for the warranty period ).

## FLIGHT BATTERY -Safety Guideline



### Warning:

Please read the ENTIRE user manual to familiarize yourself with the features of this product before use. Failure to use this product in a safe and responsible manner could result in fire, serious injury or damage to the product, or other property, please observe the following safety guidelines when using, charging, or storing the batteries.

### 1. Battery Use

- Do not allow the batteries to come into contact with any kind of liquid.
- Do not drop the battery into water.
- Do not leave batteries out in the rain, or near a source of moisture. If the inside of the battery comes into contact with water, chemical decomposition may occur, potentially resulting the battery catching on fire, and may even lead to an explosion.
- Never use non-Swellpro batteries. New batteries can be purchased by going to [www.swellpro.com](http://www.swellpro.com), or through your local Swellpro dealer. Swellpro takes no responsibility for any damage or injury caused by using non-SwellPro batteries.

- Never use or charge swollen, leaky or damaged batteries. If your batteries are abnormal, please contact Swellpro, or a Swellpro authorized dealer for further assistance.
- The battery can be used in the temperatures ranging from -10°C to 40°C. Use of the battery in environments above 50°C can lead to a fire or explosion. Use of the battery below 10°C can lead to permanent damage.
- Never disassemble, or penetrate the batteries with sharp tools, otherwise, this may result in the battery catching fire, or even lead to an explosion.
- Electrolytes in the battery are highly corrosive. If any electrolytes make contact with your skin or eyes, immediately wash the affected area with fresh running water for at least 15 minutes, and then see a doctor immediately.
- If the battery falls into water, pick it up immediately and put it in a safe and open area. Maintain a safe distance from the battery until it is completely dry. Never use the battery again, and dispose of the battery properly as described in the Battery Disposal section below.
- Do not heat batteries. A battery fire can be extinguished using sand, or a dry powder fire extinguisher.
- Do not put batteries in a microwave oven, or in a pressurized container.
- Do not put the loose battery cells onto any conductive surface, such as a metal table.
- Do not put any conductive cables or metal objects together with batteries, where they may short-circuit against each other.
- Do not drop or strike batteries.
- Do not place heavy objects on the batteries or the battery charger.
- Clean battery terminals with a clean, dry cloth. Failure to do so may result in poor electrical contact, which could reduce the battery capacity, or damage the charger.
- Do not continue to fly the drone after the low battery alarm has been activated; this will result in over-discharging the battery, and potentially could damage the battery cells.



DO NOT continue to fly the drone after the low battery alarm has been activated, this will result in over-discharging the battery, and potentially could damage the battery cells.

## 2. Battery Charging

Attention:

- Always use a Swellpro approved charger to charge the battery of the drone, and the radio controller. Swellpro takes no responsibility if the battery is charged using a non-Swellpro charger.

- In order to avoid any potential accidents happening, please do not leave the battery charging unattended.
- Do not charge the battery near flammable materials, or on flammable surfaces, such as carpet or wood.
- Do not charge battery immediately after flight, because the battery temperature may be too high.
- Disconnect the charger when not in use. Examine and maintain the charger regularly.
- Do not clean the charger with denatured alcohol or other flammable solvents.
- Never use a damaged charger.

### 3. Battery Storage and Transportation

- Keep batteries out of the reach of children and pets.
- Do not leave the battery near heat sources, such as a furnace, heater, or exposure to strong direct sunshine, for example: in cars.
- The ideal storage temperature is 22°C ~ 28°C.
- Keep the battery in a dry and ventilated environment
- Never drop the battery into water, or store it in places where there is a possibility of water leakage.
- Do not drop, strike, impale, pierce, or manually short-circuit the battery.
- Keep the battery away from metal objects, such as watches, jewelry, and hairpins.
- Never transport a damaged battery, or a battery with power level higher than 50%.
- Do discharge the power to 50% or less before transportation.(The suggested battery voltage level of the drone is around 15.8V, and the radio controller is 7.9V)
- Do discharge the power to 50% or less when you are not going to use the drone in the coming days.

### 4. Battery Maintenance

- Never use the battery when the temperature is too high or too low.
- Never store the battery in environments with a temperature higher than 60°C .
- Do discharge the power to 50% or less when you are not going to use the drone in the coming days.
- Never store the battery for a long time after use. If need to store for long time, need to fully charge the battery and then discharge to less than 50% every one month. Otherwise the battery will become over-discharged, and ruin the battery.
- Never over dis-charge the battery, otherwise the battery cells will be damaged.
- Do not charge battery immediately after flight, because the battery temperature may be too high.

## 5. Battery Disposal

- Dispose of the battery in specific recycling boxes only after a complete discharge.
- DO NOT place the battery in regular trash containers. Strictly follow your local regulations regarding the disposal and recycling of batteries.

### Safety Operation Guideline & Disclaimer and Warning

#### Safe Operation Guidelines

##### 1. Flying Conditions and Environmental Considerations

- Fly in open spaces or above the water surface that is far away from crowds.
- Only fly the SplashDrone 3+ to a maximum altitude of 4000m above sea level.
- The operating temperature range of the SplashDrone 3+ is -10°C to 40°C.
  - Observe local regulations and flight restrictions of your Aviation Authority.

##### 2. Pre-Flight Inspection and Checks

- Make sure all batteries are fully charged.
  - Check all propellers are in good condition and correctly fastened. The edges of the propeller blades must be smooth and undamaged.
  - Manually rotate the 4 motors to ensure they can spin smoothly.
- Ensure the sealing surfaces of the cover are clean, free of dirt, sand, or any other contaminants.
- Make sure the GPS top cover is facing the front of the drone and all the screws are properly fastened.
  - Please make sure when tightening the hatch screws that they are not cross-threaded and are firmly tight, but not over-tightened.
  - Make sure the drone fuselage is sealed and that the membrane on the top of the GPS hatch is in good condition.

### 3. Flying Guide

- Many regulations require the pilot to fly a drone within line of sight. Take particular care when flying a drone out of sight.
- Unless it is an emergency, NEVER Lock or STOP the motors in flight as this will cause the drone to fall to the ground and crash.
- When the low battery level warning is activated, plan to return the drone and land safely before the battery reaches a critical level.
- The Return Home function can be used to reorient the drone towards the Home Point. By activating the Return Home function, the drone will rise to the return altitude (20m) and then turn towards the Home Point before starting its return.
- If any obstacles are in the flight path of the drone during a Return Home process, control should be regained by turning off the Return Home function.
- If you inadvertently crash your drone, lock the motors to prevent damage to the motors and propellers.
- Do not attempt to touch the motors, until the motors have stopped rotating.
- When taking-off & landing from water, avoid high-speed or abusive landings to avoid damaging the drone.
- When flying over water, avoid allowing the drone to drop or crash into the water from a high altitude as this could cause major damage to the drone.
- Don't expose the drone & battery to direct sunlight for sustained periods of time as this can raise the internal temperature of the drone to well above the operating temperature range.
- If the drone does not appear to be responding to the Remote Controller as usual, switch the Drone to ATTI flight mode and fly the drone to a safe landing location.

The possible causes for the instability or loss of control of the drone could be:

- The drone has been subjected to unstable GPS signal/s or spurious interference/effects on the Compass module during flight.
- The calibration of the drone (compass and/accelerometer) was incorrectly carried out.
- The battery cable was not correctly positioned behind the battery and as far as possible from the compass module.

Steps that can be taken to resolve the issues:

- Re-calibrate both the compass and accelerometer on the SplashDrone.
- After completing the calibration, arm the drone motors to fly in GPS mode to verify whether this phenomenon has been eliminated.

- If the abnormality remains the same, please re-locate to another place at least 5KM away and re-calibrate the SplashDrone. Following the re-calibration, please test the drone again.
- If the problem persists, please contact SwellPro or your local dealer for further trouble-shooting and solutions.

#### 4. Maintenance

- Please make sure to double check the propellers after flight. Distorted or damaged propellers should be replaced immediately.
- **After flying over the sea, sand or water, the SplashDrone and modules must be thoroughly washed with fresh water within 2 hours and dried - especially the motors, gimbals and camera.**
- **It's strongly advised to rinse the drone before the salt crystalizes.**
- **Motors are best rinsed by removing the propellers and immersing the motors one at a time into a bucket of warm water and arming the drone so the motors spin.**
- In the event of the SplashDrone not being used for a long time, please store the drone and the batteries in a dry, and ventilated environment at 20°C~28°C.
- Please refer to <Safety guideline with batteries> for further details on maintaining the batteries.

#### 5. Flight Safety

- Please make sure you have a comprehensive understanding of the SplashDrone and all the necessary measures required to implement a successful return home function in the event of an emergency.
- Please be well prepared before each flight, avoid any violent or excessive operations.
- Please maintain strict compliance with the local laws, any flying in NO-FLY ZONEs is prohibited.
- Any illegal & improper use or operation of this product is prohibited.
- Any invasion & violation against another person/s right of privacy is not allowed. Before using this product, it remains the duty of the drone pilot to comply with the local laws regarding privacy protection.
- Any invasion or flying over another person/s property is not allowed, please agree with any person/s regarding any potential breach of privacy before the proposed flight.
- DO NOT fly the SplashDrone under the influence of alcohol, drugs or any other physical or mental impediment.
- Please don't fly the drone with a malfunctioning radio controller - Please fly the drone away from crowds.

---

## Restricted Area



Airport



Crowds

## Threats to Flight Safety Scenarios



Radio signal tower



Radar



High voltage power lines



Trees



Tall buildings

---

## Disclaimer and Warning



This product is not a toy, and should only be operated by persons over the age of 18. Please keep it out of reach of children, and pay particular attention to the possible scenarios of children unexpectedly appearing during flight operations.

Be sure to read this document carefully before using the product, to fully understand your legal rights, responsibilities and safety instructions. Failure to do so may cause property damage, accidents and personal injury. Once this product is used, it is deemed that you have understood, recognized and have accepted all the terms and conditions of this statement. The user is responsible for all the consequences of his actions and the use of the product. The user agrees to use the product for his sole & legal purpose, and agrees with the terms & conditions of this agreement, and other relevant policies & guidelines that may be specified by SwellPro.

Under the maximum permission by law and approved circumstances, SwellPro is exempt of liability for any indirect, punitive, consequential, special or criminal damages, including the purchase cost, or for loss of income due to the loss of use of the drone.

SwellPro is exempt from the user's liabilities for damage(s) to person/s or property, or injuries incurred directly or indirectly from the use of this product in the following conditions:



- Damage or injuries incurred when the user/s are under the influence of alcohol, drugs or medication.
- Any malfunction caused by operators' failure to follow the guidance of the manual to assemble and set up or operate the drone as described and designed.
- Damage or injuries that may occur due to failure to study the tutorial videos and the user manual before flying the drone.
- Damage or injuries caused to a person/s or property due to failure in correctly calibrating the drone as outlined in the manual prior to flight.
- Damage or injuries incurred as a result of the use or installation of any unauthorized third party accessories or counterfeit parts - which were not provided and approved of by SwellPro.
- Damage or injuries as a result of flying the drone out of eyesight range, or more than 300m away from the controller.
- Damage or injuries caused by flying the drone in areas of magnetic fields & radio interference.
- Damage or injuries caused by flying in a NO-FLY ZONE that is regulated by local laws & rules.
- Damage or injuries including crashes, loss of control or water ingress caused by abusing or modifying the original drone structure,
- Damage or injuries caused by using broken & ageing components.
- Damage or injuries caused by continuing to fly the drone even if the low battery alarm is activated.
- Damage or injuries caused by failure to wash the components with fresh water after flying over or near the sea & corrosive waters.
- Damage or injuries that have occurred when the drone has been subjected to the following conditions or situations: collision, fire, explosion, floods, tsunamis, ice, snow, avalanche, flooding, landslide, earthquake, etc.
- Damage or injuries incurred by intentionally dropping or crashing the SplashDrone into the water from a high altitude, especially water ingress into the drone fuselage and gimbal malfunction.
- Damage or injuries incurred by intentionally dropping or crashing the SplashDrone to the ground or water from a high altitude, especially water leakage into the drone fuselage and gimbal frame as a result of this collision.
- Other Damage(s) or injuries that are not SwellPro's liability.

SwellPro products are constantly being improved. Therefore, although the latest version of this manual may contain information relating to a release of the equipment different from your own, new information is added constantly which is relevant to ALL customers.

Version	Comments
1.1	New Manual for SplashDrone 3+
1.2	Pre-release corrections
1.3	Released
1.35	Editing and additions to 2-sided calibration
1.36	Edited Return Home joystick control
1.37	Added Smooth+ Control
1.38	Updated FLIGHT BATTERY -Safety Guideline
1.39	Updated Video Transmitter Channel Selection
1.40	Updated Remote Controller Joystick Calibration Method



